



Resin Number: 43204

Last Updated: 6/29/2006

Material Number:

Page 1 of 1

DESCRIPTION

Plyophen 43204 is a liquid one-step resin in ethanol.

APPLICATION

Plyophen 43204 has been specifically designed for both high and low pressure laminating applications employing glass cloth and other reinforcing agents. Properly constructed laminates made with Plyophen 43204 display superior strength and modulus retention at operating temperatures up to 400°F. (Higher temperatures may be tolerated for short periods).

TYPICAL PROPERTIES

		<u>Test Method</u>
Viscosity @ 25°C, cps	475.00	DCT 4003F
Non Volatile, %	66.50	DCT 4005A
pH	8.55	DCT 4064A
Specific Gravity	1.13	DCT 5075
Sunshine Gel (135°C), min	950.00	DCT 5091

Durez test methods are available upon request.

STORAGE

This product is a heat reactive material and should be stored in closed containers at, or below 40°F.

PACKAGING AND SHIPPING

Available in 55 gallon steel drums, 500 pounds net. This product is DOT regulated and shipped as a FLAMMABLE LIQUID, UN1866.

READ THE MATERIAL SAFETY DATA SHEET BEFORE HANDLING,
STORING OR USING THIS PRODUCT.

